


Nordic Semiconductor nRF514 Series Matching Data Details

◆ Evaluation items and evaluation data of oscillation circuit characteristics




Evaluation item

No	Item	Symbol	Recommended conditions
1	Negative resistance	RL	The value shall be at least 5 times the product R1 specification value.
2	Oscillation margin	M	
3	Drive Level	D.L	Must be within product specifications.

To ensure safe use by our customers,
We recommend an oscillation margin of 5 times or more.

IC Type	32kHz Crystal unit			External element		Oscillation characteristics			Supply voltage (V)
	Product name	R1Max. (kΩ)	CL (pF)	Cg (pF)	Cd (pF)	RL (kΩ)	M (times)	D.L (μW)	
nRF51422	SC-32S	70	9	12	12	-964	14	0.01	3
			12.5	18	18	-560	8	0.01	
	SC-20S	70	9	12	12	-1,023	15	0.01	3
			12.5	18	18	-556	8	0.01	
	SC-16S	90	7	9	8	-1,420	16	0.01	3
			9	13	12	-943	10	0.01	
			12.5	20	18	-536	6	0.02	

◆ About circuit load capacitance



The oscillation circuit has stray capacitance.
The CL value is set considering stray capacitance.
 $CL = Cg \times Cd / (Cg + Cd) + Cs$ (pF)

$Cs \triangleq$ Circuit stray capacitance

What is floating capacity?

Cos : 32kHz_IN-32kHz_OUT Stray capacitance

Cgs : 32kHz_IN-Vss Stray capacitance

Cds : 32kHz_OUT-Vss Stray capacitance

:

◆Circuit board design considerations

Place the crystal unit, capacitors, and resistors as close to the Chip as possible to shorten the wiring. To prevent interference with other signal lines, do not place other signal lines in the area where the crystal unit is mounted (underside).

The oscillation circuit design is described on our website.

In addition, please use our circuit matching service. For details, please contact our sales representatives or visit our website.

◆Caution

The above evaluation results are reference values evaluated on specific samples and "IC manufacturer's evaluation board",

They are subject to change depending on the customer's board design.

Please note that the capacitance values and characteristics of external elements may vary depending on differences in stray capacitance and other factors in actual circuit boards.

Seiko Instruments Inc.

Phone: +81-43-211-1207(Direct)

<https://www.sii.co.jp/en/quartz/>