

(Liner-free) Label / Receipt Printer

SLP720RT Series



POS/ECR

Measuring
Instrument

Barcode

KIOSK
System

Label

Medical
Equipment

- Compatible with Restick Liner-free Label, Receipt paper, Label paper with Liner
- Outside diameter of paper roll : (max.) Φ 102mm
- Printing speed : 200mm/sec(max)
- Compact : (W)90mm×(D)200mm×(H)141mm
- Cutter lock : Automatic restoration
- Paper-saving : Top margin saving (min. 4mm) & reduction of line spacing for efficient print layout
- Label taken sensor : Waits the next print job until a label is taken, prevents labels from sticking to each other
- Label editor available (for Windows, iOS/iPadOS, Android)
- Various drivers and wide variety utility software

SLP720RT
SLP721RT

Model		SLP720RT	SLP721RT
Printing	Method	Thermal line dot printing	
	Resolution [dpi]	203(8dots/mm)	
	Paper width (Printing width) [mm]	Restick liner-free label, Receipt paper : 40 (36) , 58 (54) Label (Liner width) : 31 to 58	
	Speed [mm/sec] max	200	
	Outside diameter of paper roll [mm] max	Φ 102	
	Character matrix [H×W dots]	24 X 12, 24 X 24, 16 X 8, 16 X 16	
	Character size [H×W mm]	3.0 X 1.5, 3.0 X 3.0, 2.0 X 1.0, 2.0 X 2.0	
Paper	Media Type	Restick liner-free label, Receipt paper, Label with liner	
	Top margin [mm] min	Roll paper (Drop in)	
	Paper sensor	4	
Character type		Out of paper sensor, Timing mark sensor, Label taken sensor Code page (18Pages), International character, Optional font, Downloaded character, JIS 1&2 Level Kanji, Special character, User-defined character	
Barcode		UPC-A/E, JAN(EAN)8/13, ITF, CODABAR, Code39, Code93, Code128, QR code, PDF417, Maxi code, Data matrix, GS1 Databar	
Power supply		Specified AC adapter, External power (DC24 $\pm$ 10%)	
Communication interface		USB, Ethernet+USB, Wireless LAN	Bluetooth+USB
Command		ESC/POS™ (Standard mode) conformity	
Cutting	Method	Slide type	
	Cutting type	Full cut, Partial cut (Leave center point)	
Operating Temperature [°C]		5 to 45	
Service life	Abrasion resistance [km]	Restick liner-free label, Receipt paper : 100 *1	
	Paper cutting [cut]	Restick liner-free label, Receipt paper : 1,000,000 *1, liner label : 300,000 *1	
Dimensions [W×D×H mm]		90 x 200 x 141 *2	
Mass [g]		Approx. 1100	
Standard		FCC, CE, UKCA, VCCI	
Software		Windows® : Printer Driver / OPOS / POS for .NET / Utility / Layout Editor / Smart Label Creator Android™ : Printer Class Library / URL Print Agent / Layout Editor / Smart Label Creator / MAUI SDK / Utility iOS : Printer Class Library / URL Print Agent / Layout Editor / Smart Label Creator / MAUI SDK / Utility	

*1 Use recommended thermal papers. *2 Excluding protrusion

ESC/POS™: Registered trademark of SEIKO EPSON CORP.
Windows® is the registered trademark of Microsoft Corporation(USA).

Android™ is a trademark of Google Inc.

IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Interface

Interface	Model
USB	SLP720RT-U
Ethernet+USB	SLP720RT-E
Wireless LAN	SLP720RT-W
Bluetooth+USB	SLP721RT-B

Specifications are subject to change without notice.



Seiko Instruments Inc.

Print System Division

563, Takatsukashinden, Matsudo-shi, Chiba 270-2222, Japan

Telephone:+81-47-709-0925 Facsimile:+81-47-709-1793

<https://www.sii.co.jp/sps/eg/>

Seiko Instruments U.S.A., Inc.

21221 S. Western Ave., Suite 250, Torrance, CA 90501, USA.

Telephone:+1-310-517-7778 Facsimile:+1-310-517-8154

<https://sii-thermalprinters.com/>

Seiko Instruments GmbH

Siemensstrasse 9 D-63263 Neu-Isenburg, Germany

Telephone:+49-6102-297-0 Facsimile:+49-6102-297-50100

E-mail : info@seiko-instruments.de<https://www.seiko-instruments.de>

Seiko Instruments Trading (H.K.) Ltd.

7 / F, Ying Industrial Building, 802 Lai Chi Kok Road, Kowloon, Hong Kong

Telephone:+852-2494-5160 Facsimile:+852-2424-0901

Seiko Instruments Taiwan Inc.

2F., No. 143, Changchun Rd.,

Taipei, Taiwan R.O.C.

Telephone:+886-2-2563-5001 Facsimile:+886-2-2563-5580

<http://www.sii.com.tw/en/index.html>