

3inch Mobile Label Printer

MP-B30L

Measuring
InstrumentPDA/
Smart Device

Barcode

Mobile
Printer

Label

Medical
Equipment

- Ultra Small Mobile Label Printer
- Compact & Light Weight
- Drop rating: 1.8m(6feet), IP rating: IP54
- Printing Speed: 130mm/sec max
- Simple Operation & Stylish Design
- Option Cradle for Charging



MP-B30L

Made for
iPod iPhone iPad

Model		MP-B30L
Printing	Method	Thermal line dot printing
	Number of dots/line	576
	Resolution (dots/mm)	8
	Paper width (mm)	80 ⁺⁰ ₋₁ / 76.2 ⁺⁰ ₋₁ *1 / 58 ⁺⁰ ₋₁ *1
	Printing width (mm)	72
	Printing speed (mm/sec) max	130
	Outside diameter of paper roll (mm)max	Φ51
	Character matrix (HxW dots)	24 × 12, 24 × 24, 16 × 8, 16 × 16
	Character dimensions (H×W mm)	3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0
Type of paper		Roll paper, Label roll paper
Character type		Code page(17pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character
Barcode		UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128,PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar, AZTEC
Power supply		Li-ion Battery
Communication interface		USB, Bluetooth®, W-LAN *2
Input buffer		4K bytes
Command		ESC/POS™ conformity, ZPL II™ conformity, CPCL conformity
Cutting method		Tear bar
Falling resistance		1.8m *3
IP rating		IP54 *3
Operating Temperature (°C)		-20 to 55
Service life: Abrasion resistance (km)		50 *4
Dimensions (W×D×Hmm)		105 x 126 x 58 *5
Mass (g)		395 *5
Standard		FCC, CE, VCCI
Bundled item		AC adapter, Battery, USB cable, Belt clip, Sample roll paper
Option		Cradle for charging, Single battery charger, Quad battery charger, Strap, Carrying case
Software		Windows: Printer Driver / OPOS / POS for .NET / Utility / Layout Editor Android: Printer Class Library / URL Print Agent / Layout Editor / MAUI SDK / Utility iOS: Printer Class Library / URL Print Agent / Layout Editor / MAUI SDK / Utility

*1 with Partition plate (option) *2 Selected model. *3 This number is test result based on SII procedures, not guaranteed value.
*4 Use recommended thermal papers *5 Excluding protrusion *6 with battery, without paper roll

ESC/POS™ is a registered trademark of SEIKO EPSON Corporation.
Windows® is a registered trademark of Microsoft Corporation(USA).

Android™ is a trade mark of Google Inc.

iPad, iPhone, iPod are trademarks of Apple Inc., registered in the U.S. and other countries.
iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Specifications are subject to change without notice.



Seiko Instruments Inc.

Print System Division

563, Takatsukashinden, Matsudo-shi, Chiba 270-2222, Japan

Telephone:+81-47-709-0925 Facsimile:+81-47-709-1793

<https://www.sii.co.jp/sps/eg/>

Seiko Instruments U.S.A., Inc.

21221 S. Western Ave., Suite 250, Torrance, CA 90501, USA.

Telephone:+1-310-517-7778 Facsimile:+1-310-517-8154

<https://sii-thermalprinters.com/>

Seiko Instruments GmbH

Siemensstrasse 9 D-63263 Neu-Isenburg, Germany

Telephone:+49-6102-297-0 Facsimile:+49-6102-297-50100

E-mail : info@seiko-instruments.de<https://www.seiko-instruments.de>

Seiko Instruments Trading (H.K.) Ltd.

7 / F, Ying Industrial Building, 802 Lai Chi Kok Road, Kowloon, Hong Kong

Telephone:+852-2494-5160 Facsimile:+852-2424-0901

Seiko Instruments Taiwan Inc.

2F., No. 143, Changchun Rd.,

Taipei, Taiwan R.O.C.

Telephone:+886-2-2563-5001 Facsimile:+886-2-2563-5580

<http://www.sii.com.tw/en/index.html>