

DT14xxET

4 Reversible Channel Desktop HV Power Supply Family with Ethernet & Touchscreen



Simply the best Power Supply for your laboratory

Features

- 4 independent HV channels in a fully Desktop form factor
- Channel polarity independently selectable
- SHV coaxial output connectors
- Common floating return
- Very Low Ripple
- Under/overvoltage alert, overcurrent and max. voltage protection
- 2.8" color touch screen display
- Local and Remote control (USB2.0/Ethernet)
- Interlock logic for unit enable and individual channel kill

The DT14xxET is a new CAEN Power Supply Family providing 4 independent High Voltage channels in a Desktop form factor. Each channel features an independently selectable polarity and common floating return (common return insulated from the chassis ground). High Voltage outputs are delivered through SHV connectors. DT14xxET units can be controlled either locally, thanks to a 2.8" touchscreen color LCD display with a complete user interface, or remotely, via USB or Ethernet, taking advantage of the new GECO2020 Control Software. EPICS and LabVIEW are supported.

Different versions are available spanning from 500 V to 8 kV and from 20 μ A to 3 mA, meeting the needs of a wide range of applications.

Each unit is provided with Imon Zoom. This feature enhances the current monitoring, increasing the resolution of a x10 or x20 factor according to the specific model.

The HV output Ramp-Up and Ramp-Down rates can be set independently for each channel in the range 1÷500 V/s in 1 V/s steps (1÷50 V/s for DT1419ET).

Safety features include:

- **Overvoltage and Undervoltage warning** when the output voltage differs from the programmed value.
- **Programmable hardware VMAX protection limit**
- **Overcurrent detection:** when a channel attempts to exceed the programmed current limit, it signaled to be in "overcurrent" and enter in a TRIP status. The output voltage is varied to keep the current below the programmed limit for a programmable TRIP time, then the channel is switched off. If TRIP is set to "INFINITE", the channel behaves like a current generator.
- **Common Interlock logic** for channels enable/disable and individual input signal for channel Kill function.



Ethernet and USB connections for remote control
2.8" touchscreen color LCD display for local control

Model Compare

| Model | Maximum Voltage | Maximum Current | Iset/Imon Resolution | N. of Channels |
|-----------|-----------------|-----------------|------------------------------|----------------|
| DT1419ET | 500 V | 200 μ A | 5 nA (0.5 nA with Imon Zoom) | 4 |
| DT1471ET | 5.5 kV | 300 μ A | 5 nA (0.5 nA with Imon Zoom) | 4 |
| DT1471HET | 5.5 kV | 20 μ A | 1 nA (50 pA with Imon Zoom) | 4 |
| DT1470ET | 8 kV | 3 mA | 50 nA (5nA with Imon Zoom) | 4 |

Ordering Option

| Code | Description |
|--------------|---|
| WDT1419ETXAA | DT1419ET - 4 Channel 500V/200uA Desktop HV Power Supply Unit with Ethernet & Touchscreen |
| WDT1471ETXAA | DT1471ET - 4 Channel 5.5kV/300uA Desktop HV Power Supply Unit with Ethernet & Touchscreen |
| WDT1471HETXA | DT1471HET - 4 Channel 5.5kV/20 μ A Desktop HV Power Supply High Accuracy Unit with Ethernet & Touchscreen |
| WDT1470ETXAA | DT1470ET - 4 Channel 8kV/3mA (9W max) Desktop HV Power Supply Unit with Ethernet & Touchscreen |



All CAEN Control Software are available for **free download** on the web site.

Control Software available: GECO2020 with user friendly GUI and CAEN HV Wrapper library for custom SW development. EPICS and LabVIEW also supported



DT14xxET Family, full front view



News from Catalog web page
www.caen.it/news

35 years
always at your side

LabVIEW™ is a trademark of National Instruments. Neither CAEN, nor any software programs or other goods or services offered by CAEN, are affiliated with, endorsed by, or sponsored by National Instruments.

Small details
Great differences

CAEN SpA
Via Vetraia 11
55049 - Viareggio • Italy
Phone +39.0584.388.398
Fax +39.0584.388.959
info@caen.it
www.caen.it

CAEN GmbH
Klingenstraße 108
42651 - Solingen • Germany
Phone +49.212.2544077
Fax +49.212.2544079
info@caen-de.com
www.caen-de.com

CAEN Technologies, Inc.
1140 Bay Street - Suite 2C
Staten Island, NY 10305 • USA
Phone +1.718.981.0401
Fax +1.718.556.9185
info@caentechnologies.com
www.caentechnologies.com

Copyright © CAEN SpA - 2015
All rights reserved. Information in this publication supersedes all earlier versions. Specifications subject to change without notice.
Printed in March 2015 - ADOCUME00106 - BF3257 - rev03